Advantages of LFP Over SLA

POWERED

STAY


- Lower cost per cycle, greater than ten times the cycle life of sealed lead-acid batteries
- Ultra-light weight; Significantly lighter than sealed lead-acid batteries
- Drop in replacement for sealed lead-acid batteries
- Can use the same charger as sealed lea-acid batteries in most cases (limited to a voltage of 14.6 volts)
- · Faster charging as a result of higher charge current
- More usable capacity sealed lead-acid battery capacity decreases as discharge current increases
- Includes Battery Management System (BMS) protection. Contains a circuit that fully protects itself with a Low Voltage Disconnect and a High Current Disconnect on discharge
- · Balancing circuit on charge
- 9 Ah size case

Specification

Nominal V	/oltage	12.8 Volts												
Nominal C	apacity	77º F (25º C)												
20-hr.	(.60 A)			12.0 Ah										
10-hr.	(1.2 A)			12.0 Ah										
5-hr.	(4 .0A)	12.0 Ah												
2-hr.	(5.7 A)	11.4 Ah												
Approxim	ate Weight	2.8 lbs (1.27 kgs)												
Internal R	esistance (a	≤100mΩ												
Shelf Life	Shelf Life (% of normal capacity at 68° F (20° C)													
3 N	lonths	Months	12 Months											
979	%	9	5%	85%										
Temperat	Temperature Dependency of Capacity													
-10°	С	-0°C	25°C	55°C										
509	%	65%	100%	95%										

Battery Certifications	UN38.3
Cell Certifications	IEC62133-2:2017; UL 1642
LFP Operational Temperatu	ire
Charge	32°F to 113°F (0℃ to 45℃)
Discharge	-4°F to 140°F (-20°C to 60°C)
LFP Storage Temperature	14°F to 95 F° (-10°C to 35°C)
Charge Method (Constant Vo	oltage)
Cycle Use (Repeating Use)	
Initial Current	6 A or smaller
Control Voltage	14.6 V
Float Use	

Physical Dimensions: in (mm)



L: 5.94 in (151mm) W: 2.56 in (65 mm) H: 3.74 in (95 mm) TH: 4.00 in (103 mm) Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.


*⁄

ISO 9001


Terminals

Control Voltage

F Series (Faston Tabs)



13.8 V





ue to continuous improvements to our products, product may vary slightly from depiction.

1	A	Ш	S	;p	e	C	fi	С	а	ti	0	n	S	З	ar	е	1	SI	u	b	je	еС	;t	t	С	С	;h	8	ır	10	IE	<u>,</u>	W	it	h	C)L	ıt	ľ	10	ot	ic	Э	<u>)</u> .
												-				-	- 1				·				-			-	-	- 7	-	-	-			-	-				-			

488 S. Royal Lane Coppell, Texas 75019 P 469.892.1122 T 866.892.1122 F 469.892.1123 sales@upgi.com Copyright©2019 Universal Power Group, Inc. All rights reserved.

UPG No. 48042

LiFePO4 Lithium Battery

Maintenance-Free

LEP12120